DIMM DDR3
PC3-10660 1333 MHz

Features

- Fully PC3-10660 Compliant
- JEDEC-Standard 240-pin Dual Inline Memory Module (DIMM)
- Unbuffered
- Cas Latency 9
- Power Supply: 1.5V ± 0.2V
- Pure Power and Ground Planes
- Gold PCB connector

Ordering Information

	DENSITY	REFERENCE	EAN
Optima	1GB	DIM101GBN/10660/3CBX	3536401460770
Optima	2GB	DIM102GBN/10660/3CBX	3536401460756
Premium	1GB	D1GBN08Q1333H-SB	3536401460787
Premium	2GB	D2GBN16Q1333H-SB	3536401460763
Premium	Kit 3GB (3x1GB)	KD3GBN08Q1333H-SB	3536401462446
Premium	Kit 4GB (2x2GB)	KD4GBN16Q1333H-SB	3536401002666
Premium	Kit 6GB (3x2GB)	KD6GBN16Q1333H-SB	3536401462453

Some of our capacities are also available in Premium packagings for distribution and integration purposes. Premium range modules are supplied without cooling kits. For more informations, please contact us.

Optima packaging

Premium packaging

Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

Not sure of your memory needs ?

Try our online configurator !

PNY.EU

For more information, visit : WWW.PNY.EU

PNY Technologies Europe - RCS Bordeaux B394790430. PNY, PNY Technologies and the PNY logo are registered trademarks of PNY Technologies Inc. All other trademarks and logos are the property of their respective companies. Copyright©2009 PNY Technologies, Inc. All rights reserved.